VERIFICATION OF TRANSLATION

I,   the undersigned, Marie-Claude NIEPS

of   Cabinet BEAU de LOMENIE, 158 rue de l'Université,
     75340 PARIS CEDEX 07, France,

declare as follows :

that I am well acquainted with both the English and French languages, and

that the attached document is a true and correct translation made by me to the best of my knowledge and belief of

International Patent Application N° PCT/FR2004/002572.

April 4, 2006
....
          (Date)

....
(Signature of translator)

VARIABLE-STIFFNESS VEHICLE SUSPENSION SYSTEM.

The invention relates to a vehicle suspension of
variable stiffness, and it relates more particularly to
an improvement applied to a subassembly of such a
5   suspension, as constituted by a spring mounted to bear
against two supports.

In certain suspension systems, in particular for
cars, use is made of variable-stiffness springs, both to
obtain acceptable comfort under light loading and to
10   guarantee a minimum force between bearing points when the
suspension is in the relaxed position (when the wheel is
hanging). This minimum force is essential to ensure that
the spring is held between the two supports between which
it is installed.

15   Unfortunately, a variable-stiffness spring of the
coil type can be quite complicated in structure and
consequently expensive to manufacture.

For example, it may be necessary to shape such a
coil spring so that at least one end portion thereof
20   presents a different pitch or presents turns of
continuously varying diameter in a helix so as to allow
said turns to become engaged in one another without
coming into contact with abutments. In this context, the
invention makes it possible at least to simplify spring
25   design and consequently to make a spring easier and less
expensive to produce. Advantageously, the invention
makes it possible in numerous suspension configurations
to make use of coil springs that are very simple to
produce, i.e. springs of constant stiffness.

30   More particularly, the invention relates to a
vehicle suspension comprising a coil spring mounted
between two supports of variable spacing, the suspension
being characterized in that at least one of the ends of
said spring bears against a corresponding one of said
35   supports via an elastically deformable bushing of
variable stiffness and presenting significant variation

in stiffness, said bushing being secured to the corresponding support.

The term "significant variation in stiffness" is used to mean that the bushing acts effectively in varying the overall stiffness of the complete subassembly (spring and bushing(s)). The mean stiffness of such a bushing is thus of the same order of magnitude as that of the spring, although in most cases it is significantly smaller in order to act over at least a portion of the deflection stroke of the subassembly. In particular, such bushings are advantageous for giving a particular configuration to the variation in the stiffness of the subassembly when under light loading.

As mentioned above, said spring may be of the constant stiffness type.

Advantageously, a said bushing is interposed between each said support and the corresponding end turn of said spring.

In one possible embodiment, said bushing comprises a thick annular base of elastomer material or the like, that is elastically deformable. The variation in the stiffness of the bushing can thus depend in part on its shape. For example, the base may include an annular recess.

The invention can be better understood and other advantages thereof appear better in the light of the following description given purely by way of example and made with reference to the accompanying drawing, in which:

· Figure 1 is a diagram of a portion of a suspension in accordance with the invention, and more particularly of a subassembly including a spring mounted between two supports;

· Figure 2 is a view analogous to Figure 1, the spring being compressed;

· Figure 3 is a graph showing the stiffness of the
subassembly as a function of the compression state
thereof;

· Figure 4 is a view of a bushing in a non-stressed
state, in one variant; and

· Figure 5 shows a subassembly analogous to that of
Figure 1, in a trailed-arm suspension.

In the drawings, and more particularly in Figures 1
and 2, there is shown very diagrammatically a portion of
a rear axle suspension for a vehicle, in particular a
subassembly 11 comprising a coil spring 13 mounted
between two supports 14, 15 of variable spacing.

According to a remarkable characteristic of the
invention, at least one of the ends of the spring 13
bears against a corresponding one of said supports 14, 15
via an elastically deformable bushing 17 of variable
stiffness and secured to the support. Variation in the
stiffness of the bushing must be significant over a
portion of the relative displacement between the two
supports.

In the example, both supports 14 and 15 are provided
with respective ones of such bushings 17.

The variation in the stiffness of the or each
bushing must be significant over a fraction of the
relative displacement stroke between the two supports, in
particular when the coil spring 13 is under light stress,
i.e. when it is practically relaxed. In other words, the
variable stiffness of the bushings 17 (being flattened to
a greater or lesser extent) is used over a range of
variation in which said stiffness remains of the same
order of magnitude as the mean stiffness of the spring
itself, although in this case it is substantially smaller
than that. In the example shown, the coil spring 13 is
of the constant stiffens type. Very simply, a bushing 17
comprises a thick annular base 19 of elastomer material
or the like, that is elastically deformable, i.e. that is
capable in particular of being flattened with a variable

stiffness characteristic until it reaches a state of maximum compression in which all elasticity disappears. The elastomer material selected and the thickness selected for the elastomer material can serve to determine the variable stiffness characteristic thereof as a function of the extent to which the bushing is flattened. In the present example, and as shown in Figures 1 and 2, the base 19 may constitute a simple annular block of compressible elastomer material engaged on a stud projecting from the support, the stud being defined by a plunged boss 21. The bushing is even made as a single piece of such an elastomer material and the corresponding end of said spring comes to bear thereagainst. Preferably, and as shown, the bushing includes an annular groove 23 shaped and dimensioned to receive the corresponding end turn of said spring. The deformation of the bushing can be seen by comparing Figures 1 and 2.

Figure 4 shows a variant of the bushing 17 in which the desired variation in stiffness is also obtained in part by the specific shape of the base. The base includes an annular recess 25 in its thickness, in this case a single annular groove opening out into its face that comes into contact with the support 14 or 15. This groove may be replaced by a series of recesses or cavities that are regularly distributed circumferentially.

In the examples described, the subassembly has two bushings 17, each being interposed between one of the supports 14, 15 and the corresponding end turn of said spring 13.

Under such conditions, and in very general manner, if the stiffness of the spring is Rr and if the stiffnesses of the bushings are respectively R1 and R2, the overall stiffness R of the subassembly 11 is expressed as follows:

$$R = 1/((1/R1) + (1/Rr) + (1/R2))$$

By selecting appropriate values for Rr, R1, and R2
(as a general rule R1 = R2 since the bushings are
identical) it is possible to obtain a curve for variation
in the overall stiffness of the subassembly 11 as shown
in Figure 3 in which, advantageously, the stiffness R
increases over a range corresponding to the suspension
being compressed by a small amount C (the spring is
practically relaxed, i.e. the wheel is hanging) until it
stabilizes on the stiffness Rr of the spring itself
(which in this case is constant). The rising curved
portion of the curve corresponds to the bushings
deforming, while the spring compresses hardly at all
because its stiffness is significantly greater than
theirs. When the bushings are completely compressed, the
stiffness R of the subassembly becomes equivalent to that
of the spring, i.e. it becomes constant.

Figure 4 shows the application of the principle of
the invention to a vehicle rear axle suspension in which
one of the supports moves relative to the other along a
curved trajectory, as for example in a trailed
suspension, where the suspension can open to large
angles. More precisely, in this example, the support 14
is stationary relative to the vehicle chassis, while the
other support 15 is defined on a pivot arm hinged to the
same chassis. The invention is particularly advantageous
for this type of suspension. In particular, the spring
13 bearing via the two variable-stiffness bushings 17
makes it possible to maintain contact between the end
turns of the spring 13 and the bushing 17, and between
said bushings and the supports 14, 15 by means of the
bushings deforming in non-axially symmetrical manner, in
particular in an extreme position with a hanging wheel
(as shown in Figure 5) where the spring is fully relaxed.
The deformations of the bushings present the spring
becoming detached. In this position, the subassembly 11
maintains some minimum level of loading, due essentially
to the compression of the bushings.

Other things remaining equal, this arrangement guarantees acceptable comfort when unloaded and enables a suspension mechanism to be designed that is more compact (smaller height), which constitutes a major advantage when designing the rear axle of a motor vehicle. Conversely, the invention also makes it possible to stiffen the suspension when overloaded.